# **KESENS**

## 多通水阀

#### **Electric Multi Way Coolant Valve**



### 产品介绍 Product Description

多通水阀主要包含: 电机、控制器、电路板及阀体结构。

The electric multi way coolant valve mainly includes: motor, controller, circuit board and valve body structure.

### 产品特征及优势 Feature and Benefits

- 采用直流微型电机,精准控制阀芯开度,从而精准控制流道流量。
  Using DC micro motor, the valve core opening is precisely controlled, so as to accurately control the flow of the flow channel.
- 产品自带位置反馈,电路短路、断路、过压、欠压等不良反馈。
  The product comes with position feedback, short circuit, open circuit, overvoltage, undervoltage and other bad feedback.
- 可定制的流通模式,并进行流道的切换。 Customizable circulation mode and channel switching.
- 密封结构全新设计,保证产品低内漏。 Newly designed sealing structure ensures low internal leakage of the product.

#### 产品应用 Product Application

- 切换不同管路。
  - Switch between different pipelines.
- 多模式设计,减少能源的消耗。
  Multiple circulation mode designs to reduce energy consumption.

#### 操作 Operation

#### 基本原理 Basic Principle

实现五通及以上,多模式的冷却液流道切换。

Realize multi-mode switching of coolant flow channels with five or more pipe openings.

#### 包装选项 Packaging Options

可提供定制包装以满足任何需要,请联系KESENS技术部了解详情。

Custom packaging can be provided to meet any need, please contact KESENS Engineering for details.

10000100110011000001000000



## 技术参数 Technical Characteristics

项目ITEMS	参数PARAMETER
通讯方式 Communication Method	LIN/PWM
工作电压 Operating Voltage	DC 9~16V
环境温度 Ambient Temperature	-40°C~120°C
工作温度 Temperature Range	-40°C~115°C
爆破压力 Burst Pressure	> 800kPa
最大工作压力 Max Working Pressure	500kPa
切换时间 Switch Time	≤10s
外漏 External Leakage	≤2mL/min@300kPa (air)
防护等级 Degree Of Protection	IP6K9K
寿命次数 Lifetimes	>200k cycles

可根据客户需求定制产品,如有需求请联系我们。 Customized products available upon request. Contact us for details.

地址: 浙江省嘉兴市经济技术开发区天枢路199号

Add: No. 199, Tianshu Road, Economic and Technological Development Zone, Jiaxing City, Zhejiang Province, China.

电话(Tel): 0573-82858999 邮箱(E-mail): info@kesens.com 网址(Web): www.kesens.com



2